


中载型 (M01型 - M02型)

■ 产品特点: 适用于对温度有要求的环境。



TEM01-TEM02
中载型

订购编号示例 **1**代号 - **2**轮径代号 - **3**安装代码
TEM02 - 50 - 1

1 代号	2 轮径代号	D		E	L	负载 (kg)	芯子材料	胎面材料	滚动轴承	适用温度	胎面硬度	3 安装代码	
		英寸	mm									0	1
TEM01	30	3"	75	30	41	90	/	HP 耐高温	滚轴	210℃	67D	0	定向
	40	4"	100			1						平顶万向	
	50	5"	125			3						螺杆万向	
TEM02	30	3"	75			90	/	HP 耐高温	滚轴	268℃	67D	5	插杆万向
	40	4"	100			3						螺杆万向	
	50	5"	125			7						通孔万向	

脚架说明

脚架材料	方板厚	支架厚	支架宽度	螺纹孔直径	适用标准	载重量说明	
冷轧板	4	2.5	41	3/8	GB/T14687-2011	单脚轮载重 = 总载重量 / 3	静载重 = 动载重 × 2

▲ 表面镀锌: NSS 中性盐雾实验 24h

安装尺寸图

平顶安装			螺杆安装																																															
<table border="1"> <thead> <tr> <th>D</th> <th>H</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>3"</td> <td>108</td> <td>34.5</td> </tr> <tr> <td>4"</td> <td>133</td> <td>36</td> </tr> <tr> <td>5"</td> <td>160</td> <td>36.5</td> </tr> </tbody> </table>			D	H	B	3"	108	34.5	4"	133	36	5"	160	36.5	<table border="1"> <thead> <tr> <th colspan="2">标配螺杆</th> </tr> <tr> <th>M</th> <th>L</th> </tr> </thead> <tbody> <tr> <td>3/4" M12</td> <td>25</td> </tr> <tr> <td>5" M16</td> <td>25</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="4">备选螺杆</th> </tr> <tr> <th>M</th> <th colspan="3">L</th> </tr> </thead> <tbody> <tr> <td>M12</td> <td>/</td> <td>38</td> <td>50</td> </tr> <tr> <td>M14</td> <td>25</td> <td>/</td> <td>/</td> </tr> <tr> <td>M16</td> <td>/</td> <td>38</td> <td>50</td> </tr> <tr> <td>1/2-12BSW</td> <td>1"</td> <td>1.5"</td> <td>/</td> </tr> </tbody> </table> <p>▲ (1) 六角对边 S=24mm (2) 安装必须加垫片</p>				标配螺杆		M	L	3/4" M12	25	5" M16	25	备选螺杆				M	L			M12	/	38	50	M14	25	/	/	M16	/	38	50	1/2-12BSW	1"	1.5"	/
D	H	B																																																
3"	108	34.5																																																
4"	133	36																																																
5"	160	36.5																																																
标配螺杆																																																		
M	L																																																	
3/4" M12	25																																																	
5" M16	25																																																	
备选螺杆																																																		
M	L																																																	
M12	/	38	50																																															
M14	25	/	/																																															
M16	/	38	50																																															
1/2-12BSW	1"	1.5"	/																																															
通孔安装			插杆安装																																															
<table border="1"> <thead> <tr> <th>D</th> <th>H</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>3"</td> <td>104</td> <td>34</td> </tr> <tr> <td>4"</td> <td>129</td> <td>36</td> </tr> <tr> <td>5"</td> <td>156</td> <td>36</td> </tr> </tbody> </table>			D	H	B	3"	104	34	4"	129	36	5"	156	36	<table border="1"> <thead> <tr> <th>D</th> <th>H</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>3"</td> <td>107</td> <td>34</td> </tr> <tr> <td>4"</td> <td>132</td> <td>36</td> </tr> <tr> <td>5"</td> <td>159</td> <td>36</td> </tr> </tbody> </table>				D	H	B	3"	107	34	4"	132	36	5"	159	36																				
D	H	B																																																
3"	104	34																																																
4"	129	36																																																
5"	156	36																																																
D	H	B																																																
3"	107	34																																																
4"	132	36																																																
5"	159	36																																																

▲ 定向型安装尺寸与平顶万向型安装尺寸相同