



## 内径 G6 外径 p6/ 内径 G6 外径 m6

产品特点：防止脱落用的肩型规格。

代号	类型	材质	内径公差	外径公差	硬度 HB	使用温度范围 (°C)
OFBHD OFBHDM	肩型	高力黄铜 (SP2)	G6	p6 m6	≥ 210	-50~+150



▲ 配套轴公差推荐 (仅供参考):  
 ▲ d8: 一般用 (重载); e7: 一般用 (轻载); f8: 高精度用;  
 ▲ g6: 高精度用 (间隙负载)。

### 订购编号示例

1 代号 - 2 d - 3 L

OFBHD - 15 - 30

▲ 根据命名规则选择所需规格后进行订购。

1 代号	2 dG6		Dp6		3 L										H	T		
OFBHD	5	+0.012	10	+0.024	5	6	8	10	12							14	3	
	6	+0.004	10	+0.015	5	6	8	10	12	15								14
	8	+0.014	12	+0.029 +0.018	5	6	8	10	12	15	16	20					16	4
	10	+0.005	15		6	8	10	12	15	16	20	25				19		
	12	+0.017 +0.006	18	8	10	12	15	16	20	25	30				22			
	13		22	10	12	15	16	20	25	30				26				
	15	25	+0.035 +0.022	12	15	16	20	25	30	35					30	5		
	16	26		12	15	16	20	25	30	35					30			
20	+0.020 +0.007	30	+0.042 +0.026	12	15	16	20	25	30	35	40				35	6		
25		35		15	16	20	25	30	35	40				40				

1 代号	2 dG6		Dm6		3 L										H	T		
OFBHDM	5	+0.012	10	+0.015	5	6	8	10	12							14	3	
	6	+0.004	10	+0.006	5	6	8	10	12	15								14
	8	+0.014	12	+0.018 +0.007	5	6	8	10	12	15	16	20					16	4
	10	+0.005	15		6	8	10	12	15	16	20	25				19		
	12	+0.017 +0.006	18	8	10	12	15	16	20	25	30				22			
	13		22	10	12	15	16	20	25	30				26				
	15	25	+0.021 +0.008	12	15	16	20	25	30	35					30	5		
	16	26		12	15	16	20	25	30	35					30			
20	+0.020 +0.007	30	+0.025 +0.009	12	15	16	20	25	30	35	40				35	6		
25		35		15	16	20	25	30	35	40				40				